COLONIA DE LA COLONIA DE LA C

POWERSCAN™ 7000 / 7100

PD7100

PBT7100

7000 2D

* MOBILITY / RANGE											
SHORT R	ANGE	M	EDIUM RANGE	LONG RANGE							
Up to 12 n	n/40 ft	Up t	o 30 m/ 98.4 ft	Up to 100 m/328 ft							
** READING RANGE											
CONTACT	INSTINCTIVE		DISTANCE	LONG Range	AUTO RANGE						
0-5 cm/ 0-2 in	0-30 c 0-12		0-100 cm/ 0-39 in	0-250 cm/ 0-98 in	Up to 10 m/ 33 ft						

	SHORT RANGE Up to 12 m/40 f	t Up to 30 m/ 98.4 ft Up to 100 m/328 ft ** READING RANGE		Also Available in Black	Also Available in Black	7						
V		0 cm/ 0-100 cm/ 0-250 cm/ Up to 10 m/ 0-99 in 0-99 in Up to 10 m/ 33 ft ended Products	handheld data collection pro	product series are Datalogic's v ducts. The PowerScan 7000 / 7 ability and extremely snappy re	100 1D and 2D imaging	reliable feedback featuring t	res and performance for indust ne 'Green Spot' on the code con e. Includes a loud beeper for ad	nbined with dual good-read LE	GL™ (Three Green Lights) techno Ds on top and on the back of th	logy ensure quick and e cap for increased visibility	The PowerScan DPM reade imagers specifically addres codes marked with DPM (D	ssed and capable o
		Technology	Area Imager	Linear Imager	Linear Imager	Laser	Laser	Laser	Area Imager	Area Imager	Area Imager	Area Ima
		Mobility / Range* (see chart at top)	Corded	Corded	*Bluetooth / Long	Corded	*Bluetooth / Long	*STAR / Medium	*STAR / Medium	Corded	Corded	Corde
Ē	CT HIGHLIGHTS	Distinctive Features	Standard Range and High Density optics VGA resolution plus image capture for multiple uses including signature capture Decodes 1D, 2D, postal codes and OCR fonts	Excellent reading performance for high speed applications Wide scan angle and superior depth of field in the same model Optional aiming system	All the same features as PD7100 Point-to-point and point-to-multi-point communications	Choice of Standard or Auto Range optics Dual-position trigger for code aiming Wide temperature range perfect for operation in refrigerators Undecoded Laser Output model	 All the same features as PD8300 Optional display with 3 or 16-Key keypads Bluetooth 2.0 compliant Point-to-point and multipoint transmission Piconet with up to 4 devices 	 All the same features as PD8300 Optional display with 3 or 16-Key keypads Point-to-point, point-to multi-point and network communications Up to 255 devices Two-way communications 	 Optional display with 3-Key keypad Point-to-point, point-to-multi-point and network communications Up to 255 devices Two-way communications 	Fixed focus and autofocus models Snappy omnidirectional reading from contact to over 1.0 m / 3.3 ft Datalogic's new intuitive 'frame' aiming system with Datalogic's Motionix™ motionsensing technology 'Soft white light' illumination	 Multi-Axis Illumination technology Aggressive decoding of codes marked with DPM Industrial and rugged design Vibrating motor for noisy industrial environments USB and RS-232 interface options 	technology and
ы	Ď	Reading Range ** (see chart at top)	Instinctive	Long Range	Long Range	Distance / Auto Range	Distance / Auto Range	Distance / Auto Range	Instinctive	Instinctive / Distance	Contact	Contact / Ins
	PRODU	1D / Linear Codes	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$
	а.	2D Codes	$\overline{\checkmark}$								$\overline{\checkmark}$	$\overline{\checkmark}$
		Datalogic 'Green Spot' Technology		$\overline{\checkmark}$					$\overline{\square}$	$\overline{\checkmark}$		$\overline{\checkmark}$
		Remote Host Download		$\overline{\checkmark}$								$\overline{\checkmark}$
		Environmental Protection	IP65	IP65	IP65	IP65	IP64 / IP65	IP64 / IP65	IP64 / IP65	IP65		IP65
		Factory Warranty	5 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	2 Years	3 Year
		Point-of-Sale (POS)		Heavy Duty	Heavy Duty		Heavy Duty	Heavy Duty				i e
31	ET S	Signature / Image Capture	Heavy Duty						Heavy Duty	Heavy Duty		Heavy D
- 1	CROSS MARKET APPLICATIONS	Document Handling	Heavy Duty	Heavy Duty	Heavy Duty		Heavy Duty		Heavy Duty	Heavy Duty		l e
931	CA M	Ticketing / Access Control			Indoor / Outdoor		Indoor / Outdoor	Indoor / Outdoor				1
ю	055 055	Shipping and Receiving	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty		
ы	A G	Asset Tracking	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy D
		Warehouse Management	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty	Heavy Duty		
		ID / Age Verification (US)	O						$\overline{\checkmark}$	$\overline{\checkmark}$		
ш	_	Merchandise Returns					O	O				
	XET	Front Office		0								
ы	1AR ONS	Courier Services / Sorting	·	$\overline{\checkmark}$				$\overline{\checkmark}$	$\overline{\checkmark}$	⊙		i e e e e e e e e e e e e e e e e e e e
7	N D VI D	문 Patient Administration										
н	IZE IC	Point of Care / Bedside Bar Coding			⊙							
	SPECIALIZED MAR APPLICATIONS	Laboratory Services / Tracking	·									
	DEC.	_ Shop Floor / Work in Progress	<u> </u>	O	⊙		$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$
	_ <u>r</u>	Order Picking / Fulfillment			<u> </u>	· ·	✓	✓	<u> </u>	· ·		
		Forklift Operations		0	· · ·	\square	✓					
						<u>•</u>						

PD8300

INDUSTRIAL HANDHELD READERS

PBT8300

POWERSCAN™ 8000 / 9000

PM8300

PM8500

STATALOGIC



www.datalogic.com





POWERSCAN DPM

PD8590-DPM

PD9500

PD9530-DPM



All Datalogic ADC products support GS1 DataBar™ linear codes.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic, ADC Inc. is under

© 2013 Datalogic ADC, Inc. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic, Inc. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • PowerScan and QuickScan are registered trademarks of Datalogic ADC, Inc. in many countries, including the U.S. and the E.U. • Heron is a registered trademark of Datalogic ADC, Inc. in the U.S. ■ 3GL, Datalogic Star Cordless System and Touch are trademarks of Datalogic ADC S.r.l. • Illumix, and Motionix are trademarks of Datalogic, ADC Inc. • All other brand and product names are trademarks of their respective owners.

Product specifications are subject to change without notice.

> General Purpose & Industrial Handheld Readers



STATALOGIC

TOUCH™

TD1100

CONTINUING A LEGACY OF EXCELLENCE

Fast-paced

and dynamic,	* MOBILITY / RANGE									1 2)					(2)	
the Automatic	SHORT RANGE MEDIUM RANGE LONG RANGE	46			19 11 1											
Identification and	Up to 12 m/40 ft Up to 30 m/ 98.4 ft Up to 100 m/328 ft ** READING RANGE		-	~ D								~ 7				
Data Collection	CONTACT INSTINCTIVE DISTANCE LONG RANGE RANGE	Also Available in White							Available in Black, White or Disinfectant-Ready Enclosures	Available in Black, White or Disinfectant-Ready Enclosures	Available in Black, White or Disinfectant-Ready Enclosures	9	Available in Black, White or Disinfectant-Ready Enclosures	Also Available in White	Available in Black, White or Disinfectant-Ready Enclosures	Available in Black, White o Disinfectant-Ready Enclosu
industry requires		An excellent value for those	Entry level scanner with	The QuickScan series of econ	 nomical readers are designed for	use in retail and office environ	ments and offer snappy	Entry level readers packed		linear imagers offer fast readin		Premium features include	The Gryphon 4400 series of a			
commitment,	0-5 cm/	seeking a cost-effective	snappy performance and the	e reading performance. The QI	02300 laser model is the perfect	solution for customers who pre	efer laser scanning technology.	with features that are	1D/linear bar codes. The ext	reme versatility of the Datalog	c Gryphon combines many top	longer reading distances,	the flicker effect, features a	enter-cross aimer with four	corner dots defining the read	ling area. Datalogic's
	☑ = Recommended Products ⊙ = Alternative Products	solution.	widest scan angle/longest scan line for selected market		ading 1D and 2D bar codes and is	s the perfect solution to upgrad	le existing laser scanners to	perfect for large to small retail or POS applications.	to durability and ergonomics		llance, from reading capabilities	well-defined scan line.	Motionix™ motion sensing te	chnology automatically swite	nes between nandneid and s	stand mode.
adaptability to	Technology	Linear Imager	applications. Linear Imager	Linear Imager	Linear Imager	Laser	Area Imager	Linear Imager	Linear Imager	Linear Imager	Linear Imager	Laser	Area Imager	Area Imager	Area Imager	Area Imager
constant change.	Mobility / Range* (see chart at top)	Corded	Corded	Corded	*STAR / Short	Corded	Corded	Corded	Corded	*Bluetooth / Medium	*STAR / Medium	Corded	Corded	Corded	*Bluetooth / Medium	*STAR / Medium
Only state-of-		Cost-effective contact	• Wide scan angle / scan line	• Affordable	Most affordable cordless	■ Affordable	Affordable 2D reader	■ Handheld and hands-free	■ Superior depth-of-field	• All the same features as	• All the same features as	■ Superior depth of field	Omnidirectional reading	■ All the same features as		• All the same features
the-art solutions	_	readers Two width options for	Over mold protectionGood-read Green Spot	Replaceable windowErgonomic - lightweight	solution • Point-to-point	Replaceable windowErgonomic - lightweight	Outstanding snappinessOmnidirectional reading	operation Stand Mode automatically	 Wide scan angle Excellent reading 	Model GD4100 • Point-to-point and	Model GD4100 • Point-to-point and	Wide scan angleAggressive reading and	High motion toleranceUser friendly illumination	GD4400 All-in-One integrated	GD4400 2-Position cradle with	GD4400 2-Position cradle with
can satisfy the	_	specific code reading	Collapsible stand	with small form factor	communications	with small form factor	 Reduced visual stress with 		performance and label	point-to-multi-point	point-to-multi-point	label decoding	■ Highly visible 4-dot aimer	tilting base	Scan-While-Charging	Scan-While-Charging
ever-demanding	Distinctive Features	 Compact and innovative 'read-thru' holder for hands- 		 Excellent reading on hard- to-read codes 	Scan-While-ChargingBatch Mode	 Wider than usual scan angle for reading wider 	LED-based aiming system Advanced motion tolerance	Accurate and high first-	decoding High resolution code	communication • 2-Position cradle with	communicationOptional display with 3-Key		Image / document captureDecodes 1D, 2D, Postal,	presentation operation	Batch Mode capabilityUser replaceable Lithium-	 Batch Mode capabilit User replaceable
expectations	5 Distillctive realtires	free reading • Pro models are multi-		 Extended depth-of-field 	 Excellent reading on hard- to-read codes 	codes at short distances	optics	pass read rates • Complete data formatting	reading capability FAS option	Scan-While-Charging Batch Mode	keypad 2-Position cradle with		stacked, composite codes • Multi-interface options	 Automatic switching between handheld and 	Ion battery • Point-to-point and	Lithium-Ion battery Point-to-point and
of customers.		interface						and editing			Scan-While-Charging		■ Standard Range/High	presentation mode	point-to-multi-point	point-to-multi-point
	董										Batch ModeAnti-counterfeit option		Density option	Raised cable port	communicationHigh Density model	communicationAnti-counterfeit optic
Datalogic always goes one step	Reading Range ** (see chart at top)	Contact / Instinctive	Instinctive	Instinctive	Instinctive	Instinctive	Instinctive	Instinctive	Distance	Distance	Distance	Distance	Distance	Distance	available Distance	(433 MHz only) Distance
beyond. Dedication	1D / Linear Codes	Contact / Instinctive	III3tilictive ✓	institute ✓	III3LIIICLIVE ✓	₩ W	III SUITCUVE	₩ W	Distance ✓	✓ V	Distance ✓	Distance ✓	Distance ✓	Distance ✓	✓ V	Distance ✓
			V	V	V	V		V	V	V	V	▼				
to exceeding	2D Codes															
the customers'	Datalogic 'Green Spot' Technology						<u> </u>	\square	<u> </u>	<u> </u>	<u> </u>					\square
expectations has led	Remote Host Download						$\overline{\square}$		\square	<u> </u>		<u> </u>	<u> </u>	<u> </u>	<u> </u>	$\overline{\square}$
to the development	Environmental Protection	IP30	IP42	IP42	IP30	IP42	IP42	IP30	IP52	IP52	IP52	IP52	IP52	IP52	IP52	IP52
of the widest range	Factory Warranty Point-of-Sale (POS)	5 Years	3 Years	5 Years	3 Years	3 Years	5 Years	5 Years	5 Years	3 Years Light / Medium Duty	3 Years	5 Years	5 Years	5 Years Light / Medium Duty	3 Years Light / Medium Duty	3 Years
of high performance	Signature / Image Capture	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Dut
products and	Document Handling	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Dut
solutions in the	Ticketing / Access Control	0	Indoor	Indoor	3	Indoor	Indoor	Indoor	3	Indoor	Indoor	8 *** ***	Indoor	Indoor	Indoor	Indoor
industry. This,	Shipping and Receiving		Light Duty				Light Duty		Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Dut
combined with	Asset Tracking				Light Duty				Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Duty	Light / Medium Dut
excellent service,	ID / Age Verification (US)						$\overline{\checkmark}$						$\overline{\checkmark}$	\square	$\overline{\checkmark}$	$\overline{\checkmark}$
has made Datalogic	Merchandise Returns		0			O		O	O	$\overline{\checkmark}$		0	$\overline{\checkmark}$	$\overline{\square}$		$\overline{\mathbf{V}}$
a world leader for	Front Office	0	$\overline{\checkmark}$	$\overline{\checkmark}$		$\overline{\checkmark}$	V		$\overline{\checkmark}$			$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$		
automatic data	Courier Services / Sorting					_	_		_							
capture needs.	Patient Administration	0	$\overline{\checkmark}$	$\overline{\checkmark}$	⊙	$\overline{\checkmark}$	$\overline{\checkmark}$		$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$	$\overline{\checkmark}$
	Point of Care / Bedside Bar Coding								\square	$\overline{\mathbf{V}}$	<u> </u>		<u> </u>			\square
	Point of Care / Bedside Bar Coding Laboratory Services / Tracking		·	·		$\overline{\square}$	· ·					V		\square	· ·	<u></u>
	Shop Floor / Work in Progress (WIP)								·	\square		· ·				
	Order Picking / Fulfillment									<u> </u>						
	Forklift Operations										V				<u>V</u>	V
	POTKIIT Operations								⊙			0				

QD2400 2D

QUICKSCAN™

QM2100

QD2100

GENERAL PURPOSE HANDHELD READERS

GD4100

HERON™

D1X0

GRYPHON™ 4100

GBT4100

GM4100

GRYPHON™ 4300

GD4300

GD4400 2D



GRYPHON™ 4400

GD4400-B 2D



